

TUNES PARA

-112

## DRYING TUMBLER TK SERIES

Our friendship started with machine manufacturing and sales, will continue to increase as long as you operate your business. Since 1977, numerous domestic and international laundry facilities were founded by TEMEL MAKINE.



In electric heated models, stainless steel heating elements



777

••

Cool – down cooling system

In steam heated models stainless steel steam

Large loading door for easy load and unload

Dogu Sanayi Sitesi 12.Blok No:5-7-9 34197 Bahcelievler-Istanbul/TURKEY Tel: +90 (212) 240 20 83 pbx Fax: +90 (212) 232 19 57 www.temelmakina.com.tr

Eco-friendly l	products pro	, water po	man health
Eco-friendly and also environment MAKINE is cocilities	products pro prevent ail and also prevent ail	sent thes	e eco-friend to the future
environmen	proud to pre	portance	
MANILIES	hat 9.		

Drum volume liter 495 735 975 1210 1925   Drive motor power kw 0,75 0,75 1,1 1,5 2,2   Fan motor power kw 0,75 0,75 1,1 1,5 2,x1,5   Exhaust flow m³/h 1200 1200 1900 2400 4800   Steam consumption kg/h 45 60 90 110 190   Width mm 1060 1060 1310 1405 1620								
Drum volume liter 495 735 975 1210 1925   Drive motor power kw 0,75 0,75 1,1 1,5 2,2   Fan motor power kw 0,75 0,75 1,1 1,5 2,x1,5   Exhaust flow m³/h 1200 1200 1900 2400 4800   Steam consumption kg/h 45 60 90 110 190   Width mm 1060 1060 1310 1405 1620			TK 500	TK 700	TK 1000	TK 1200	TK 2000	
Drum volume liter 495 735 975 1210 1925   Drive motor power kw 0,75 0,75 1,1 1,5 2,2   Fan motor power kw 0,75 0,75 1,1 1,5 2,x1,5   Exhaust flow m³/h 1200 1200 1900 2400 4800   Steam consumption kg/h 45 60 90 110 190   Width mm 1060 1060 1310 1405 1620	Capacity	kg/load	25	35	50	60	100	
Drive motor power kw 0,75 1,1 1,5 2,2   Fan motor power kw 0,75 0,75 1,1 1,5 2,2   Exhaust flow m³/h 1200 1200 1900 2400 4800   Steam consumption kg/h 45 60 90 110 190 190   Width mm 1060 1060 1310 1405 1620	Drum size	mm	Ø 970 / 670	Ø 970 / 1000	Ø 1180 / 890	Ø 1280 / 940	Ø 1500 / 1090	
	Drum volume	liter	495	735	975	1210	1925	:
	Drive motor power	kw	0,75	0,75	1,1	1,5	2,2	
	Fan motor power	kw	0,75	0,75	1,1	1,5	2 x 1,5	
	Exhaust flow	m³/h	1200	1200	1900	2400	4800	
	Steam consumption	kg/h	45	60	90	110	190	:
Depth mm 1250 1560 1550 1560 1550   Height mm 2000 2000 2200 2300 2460   Net weight kg 500 650 750 950 1200	Width	mm	1060	1060	1310	1405	1620	
Height mm 2000 2000 2200 2300 2460   Net weight kg 500 650 750 950 1200	Depth	mm	1250	1560	1550	1560	1550	
Net weight ka 500 650 750 950 1200	Height	mm	2000	2000	2200	2300	2460	
	Net weight	kg	500	650	750	950	1200	:

		TK 500	TK 700	TK 1000	TK 1200	TK 2000
Capacity	kg/load	25	35	50	60	100
Drum size	mm	Ø 970 / 670	Ø 970 / 1000	Ø 1180 / 890	Ø 1280 / 940	Ø 1500 / 10
Drum volume	liter	495	735	975	1210	1925
Drive motor power	kw	0,75	0,75	1,1	1,5	2,2
Fan motor power	kw	0,75	0,75	1,1	1,5	2 x 1,5
Exhaust flow	m³/h	1200	1200	1900	2400	4800
Steam consumption	kg/h	45	60	90	110	190
Width	mm	1060	1060	1310	1405	1620
Depth	mm	1250	1560	1550	1560	1550

green living that help to conserve energy om deterioration. TEMEL products to all kinds of of the world's resources.

- Que

It has been developed for Professional laundries textile drying process

Stainless steel special perforated drum

Long life and quite operation with drum transmission system

In electric heated models, stainless steel

All non stainless steel surfaces are electrostatic painted In steam heated models stainless steel

Large loading door

**Right-left rotation** 

heating elements

Whole body is heat isolated Dual operation system; computer programmed and manual Steam valve with pneumatic piston With double vacuum motor, high aspiration

Easy cleaned filter chamber,

Heat recovery system-Optional

Cool-down system

team coil



