

BAND HEATED  
FLATWORK IRONER  
**TU SERIES**  
ELECTRIC HEATED

# Innovation

Our friendship started with machine manufacturing and sales, will continue to increase as long as you operate your business. Since 1977, numerous domestic and international laundry facilities were founded by TEMEL MAKİNE.



It has been developed for Professional laundries flat linen ironing process



Eco-friendly products promote green living that help to conserve energy and also prevent air, water pollution. They prove to be boon for the environment and also prevent human health from deterioration. TEMEL MAKİNE is proud to present these eco-friendly products to all kinds of facilities that give importance to the future of the world's resources.



- ✓ Advanced technology and high efficiency
- ✓ Maximum service in minimum area
- ✓ Simultaneously drying and ironing all types of flat linen perfectly
- ✓ Patented ironing cylinder that is produce of high heat transmission coefficient steel
- ✓ The main ironing cylinder is coated with hard chrome
- ✓ Original NOMEK drying and ironing bands
- ✓ Electronic speed adjustment according to type of linen
- ✓ Independently operating high efficiency dual-stage heating elements,
- ✓ Perfect ironing quality and energy saving with infrared heat sensor and electronic heat controller
- ✓ Silence operation and perfect ironing quality
- ✓ All painted surfaces electrostatically painted
- ✓ Machine adapted strong suction hoods and high fan motor
- ✓ At the end of operation automatic cool-down and stop system

|                               |                   | TU 5016      | TU 5021      | TU 5025      | TU 6025      | TU 6030      |
|-------------------------------|-------------------|--------------|--------------|--------------|--------------|--------------|
| <b>Capacity</b>               | kg/h              | 40           | 46           | 50           | 60           | 72           |
| <b>Cylinder size</b>          | mm                | Ø 500 / 1650 | Ø 500 / 2150 | Ø 500 / 2500 | Ø 600 / 2500 | Ø 600 / 3000 |
| <b>Ironing speed</b>          | m/min             | 2 - 12       | 2 - 12       | 2 - 12       | 3 - 15       | 3 - 15       |
| <b>Motor power</b>            | kW                | 0,75         | 0,75         | 0,75         | 1,1          | 1,1          |
| <b>Electric heating power</b> | kW                | 15           | 18           | 24           | 32           | 42           |
| <b>Fan motor power</b>        | kW                | 0,22         | 0,22         | 2 x 0,22     | -            | -            |
| <b>Exhaust flow</b>           | m <sup>3</sup> /h | 700          | 700          | 2 x 700      | 2 x 700      | 2 x 700      |
| <b>Width</b>                  | mm                | 2500         | 3000         | 3350         | 3350         | 3850         |
| <b>Depth</b>                  | mm                | 900          | 900          | 900          | 1150         | 1150         |
| <b>Height</b>                 | mm                | 1550         | 1550         | 1550         | 1650         | 1650         |
| <b>Net weight</b>             | kg                | 700          | 800          | 920          | 1100         | 1350         |

Specifications, technological innovation in line and no ads We reserve the right to change without notice.